

DNL 285

DESCRIPTION

DarNlok 285 is a water reducing admixture. DNL 285 has various uses for all types of mixers because of its rapid integrating characteristics and the ability to be used in the water supply system. Common uses for DNL 285 include mortar, counter tops, and adhesive coatings. Because DNL 285 is colorless, there is no change in the color of the mix or the color of the final product. DNL 285 decreases water/cement ratios while increasing the quality of cement and/or plaster, improving slump loss, splashing, shrinkage, segregation and stabilizing the volume.

ADVANTAGE

Increases bonding, flexural, and compressive strength. Workability, placement and finishing easier. Locks in air and water. Enhances air entrainment by 1 to 1-1/2% + -. Stabilizes the volume. Accelerates the finishing time. Enhances Color.

PHYSICAL DATA

Neutral in solution. Non-flammable. Non-toxic. Non-carcinogenic. White, medium viscosity Hygroscopic. Non-corrosive.

APPLICATION

Add to mixing water 1/2 to 1-1/2 gallons per 100 gallons of water. Add 4 to 10 oz per bag of cement.

PACKAGING

Available in 30 or 55 gallon drums and is delivered by tanker trucks for set-up customers purchasing bulk amount 300, 500, 1000 (+) gallons. Must be dispersed separately but is compatible with most admixtures.

LIMITATIONS

Freeze below 20 degrees F.

DISCLAIMER

The information in this publication is to the best of our knowledge, reliable. Users should make their own tests to determine the suitability of these products for their own particular purposes. DarCole Products, Inc. makes no warranty of any kind, express or implied, including those of merchantable and fitness for purpose. The responsibility of DarCole Products, Inc. for claims arising out of breach of warranty, negligence, strict liability, or otherwise are limited to the purchase price of the materials.

DARCOLE
PRODUCTS, INC.



P.O. Box 1460
Henderson, KY 42419-1460
Phone: (800) 327-6565 or (270) 826-6499
Fax: (270) 831-2288
Website: www.darcole.com