

# DSR

## DESCRIPTION

DarCole Surface Retarder is a nonflammable, sprayable liquid designed for applications to freshly placed horizontal concrete surfaces. DSF's special, organic formulation reacts with the cement in the surface mortar to delay initial set and remain workable for an extended period of time. When the concrete has hardened to approximately 1500 PSI, the retarded mortar paste may be removed by flushing with a gentle stream of water and/or removed by scrubbing with a stiff brush.

## ADVANTAGE

DarCole Surface Retarder is a concrete surface retarder designed to retard the initial set time of surface mortar for exposed aggregate surfaces.

## PHYSICAL DATA

Green liquid which will not discolor or stain concrete or interfere with setting or structural strength.

## APPLICATION

DarCole Surface Retarder should be used to create exposed aggregate surfaces on sidewalks, roadways, patios, and exposed aggregate panels to enhance the architectural beauty and to achieve a more slip-resistant surface.

## LIMITATIONS

Protect from freezing. **KEEP OUT OF REACH OF CHILDREN. DO NOT CONSUME. PROVIDE EYE PROTECTION.**

## PACKAGING

DarCole Surface Retarder is available in one gallon pails, 5 gallon pails, and 55 gallon drums.

## DISCLAIMER

To the best of our knowledge, the information provided in this publication is reliable. Users should make their own tests to determine the suitability of these products for their own particular purposes. Darcole Products, Inc. makes no warranty of any kind, express or implied, including those of merchantable and fitness for purpose. The responsibility of DarCole Products, Inc. for claims arising out of breach of warranty, negligence, strict liability, or otherwise are limited to the purchase price of the materials.



DARCOLE  
PRODUCTS, INC.

P.O. Box 1460

Henderson, KY 42419-1460

Phone: (800) 327-6565 or (270) 826-6499

Fax: (270) 831-2288

Website: [www.darcole.com](http://www.darcole.com)

Email: [Darcole@darcole.com](mailto:Darcole@darcole.com)